

Elys Litchi



✔ Stylish Design, Unique Experience

Litchi's sleek look comes from its suspended design. Made of aluminum alloy, it's anodized to give you a unique experience.

💻 Outstanding Setup, Excellent Performance

Features a 15.6" IPS high-definition main screen and 15.6"/10.1" associated screen to meet diverse business needs. Equipped with rich interfaces like Cash Drawer, Gigabit Ethernet Port, USB, Serial Port, etc., and compatible with various commercial peripherals.

🔒 Convenient and Secured

Utilizing IoT device access security and face recognition technology, Elys Litchi ensures safer and faster operations.

💡 Cutting-Edge System, Innovative Feature

With the adoption of Android 12 OS and integration of LinkUp, Elys Litchi achieves seamless ecological integration and collaboration, doubling business efficiency.





Elys Litchi Specifications

Model Name: L1600 / L1601 / L1602



Operating System

Android 12
Supporting Uniphiz



Processor

Quad-Core
Cortex® - A55 2.0GHz



Memory

LPDDR4X 4GB + eMMC 64GB
Optional:
LPDDR4X 2GB + eMMC 16GB
External:
MicroSD Card slot (Up to 128GB)



Displays

Main Screen: 15.6" 1920 × 1080 px IPS FHD Touch Screen
Secondary Screen:
L1600: N/A
L1601: 10.1" 1280 × 800 px IPS Screen, Optional Touch
L1602: 15.6" 1920 × 1080 px IPS Screen, Optional Touch



Cameras

Optional: Main Screen Camera: 5MP Auto Focus
Optional: Secondary Screen Camera: 5MP Auto Focus



Button

Power Button



Audio

Speaker: 3W
Microphone



Comms Configurations

WiFi 2.4GHz / 5GHz
Bluetooth 5.0



SAM

Optional: 1 * Mini SAM



Power Indicator

White LED



Ports

1 * USB Type-A 3.0 | 3 * USB Type-A | 1 * USB Type-C | 1 * LAN (1000M)
1 * DK (RJ11, 24V / 12V) | 1 * RS232(RJ45) | DC IN | Audio Jack



Environmental

Operating Temperature: 0°C ~ 50°C (32°F ~ 122°F)
Storage Temperature: -20°C ~ 70°C (-4°F ~ 158°F)
Relative Humidity: 10% ~ 93%, non-condensing



Power

Input: 100-240V AC, 1.0A
Output: 24V DC, 1.5A



Physical

364.6 × 220.0 × 322.4mm

